

AMENDMENTS TO THE CLAIMS:

Please amend claims 1, 22 and 23 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (currently amended) A transmitter apparatus comprising:
one or more lasers,
modulation means ~~to intensity modulate~~ for information modulating radiation output by
each of said one or more lasers, and
output means for outputting the modulated radiation produced by the modulation means;
and characterised in that the apparatus comprises
hollow core optical waveguides formed in a substrate ~~which, in use, guide~~ for guiding
radiation from the one or more lasers to the modulation means and from the modulation means to
the output means.

2. (previously presented) An apparatus according to claim 1 wherein at least one of the
one or more lasers and the modulation means is a discrete component.

3. (original) An apparatus according to claim 2 wherein said discrete component is
located in an alignment slot formed in the substrate.

4. (previously presented) An apparatus according to claim 1 wherein at least one of the
one or more lasers and the modulation means is a monolithic component formed in the substrate.

5. (previously presented) An apparatus according to claim 1 wherein the output means is arranged to couple the modulated radiation into at least one output optical fibre.

6. (original) An apparatus according to claim 5 wherein the output means comprises at least one fibre attachment means.

7. (original) An apparatus according to claim 6 wherein at least one optical fibre attachment means is arranged to receive a lensed output optical fibre.

8. (original) An apparatus according to claims 6 wherein at least one optical fibre attachment means comprises a mode matching means.

9. (previously presented) An apparatus according to claim 1 comprising one laser.

10. (previously presented) An apparatus according to claim 1 and comprising a plurality of lasers.

11. (original) An apparatus according to claim 10 wherein each of said plurality of lasers have a different output wavelength.

12. (original) An apparatus according to claim 11 wherein beam combining means are additionally provided to combine the plurality of modulated beams into a combined beam

wherein said output means is arranged to couple the combined beam into a single output optical fibre.

13. (previously presented) An apparatus according to claim 10 wherein said output means is arranged to couple each of said plurality of modulated beams into one of a plurality of output optical fibres.

14. (previously presented) An apparatus according to claim 1 wherein one of said one or more lasers is a semiconductor laser.

15. (original) An apparatus according to claim 14 wherein said semiconductor laser is a wavelength tuneable semiconductor laser.

16. (previously presented) An apparatus according to claim 1 wherein one or more detectors are provided to monitor the intensity of radiation output by said one or more lasers.

17. (previously presented) An apparatus according to claim 1 and further comprising at least one optical isolator.

18. (previously presented) An apparatus according to claim 1 wherein one or more beam shaping means are provided.

19. (original) An apparatus according to claim 18 wherein at least one of said beam shaping means comprise one or more lenses.

20. (previously presented) An apparatus according to claim 18 wherein at least one of said beam shaping means comprises a tapered hollow core optical waveguide.

21. (previously presented) An apparatus according to claim 1 wherein said modulation means comprises one or more electro-optic modulators.

22. (currently amended) A transmitter apparatus comprising:
at least one laser ~~capable of~~ for producing intensity information modulated radiation; and
output means for coupling the radiation produced by the laser into at least one output optical fibre; ~~and characterised in that the apparatus comprises~~
hollow core optical waveguides formed in a substrate ~~which, in use, guide~~ for guiding
radiation from the at least one laser to the at least one output optical fibre.

23. (currently amended) ~~A~~ An information modulated radiation receiver apparatus comprising:
at least one hollow core optical waveguide formed in a substrate;
one or more detectors; and
one or more optical fibre attachment means, the one or more optical fibre attachment means ~~being arranged~~ adapted to receive one or more one optical fibres, wherein said radiation is guided from the one or more optical fibres to the one or more detectors by said at least one

hollow core optical waveguide ~~formed in a substrate~~, said at least one hollow core waveguide guiding said radiation in two transverse directions.

24. (original) An apparatus according to claim 23 comprising a plurality of detectors.

25. (original) An apparatus according to claim 24 wherein a plurality of optical fibre attachment means are provided to receive a plurality of optical fibres.

26. (original) An apparatus according to claim 25 wherein, in use, radiation from each of said plurality of optical fibres is guided to one of the plurality of detectors.

27. (original) An apparatus according to claims 24 wherein one optical fibre attachment means is provided, said optical fibre attachment means being arranged to receive one optical fibre carrying radiation comprising a plurality of different wavelength channels.

28. (original) An apparatus according to claim 27 and further comprising wavelength demultiplexing means, said wavelength demultiplexing means being arranged to separate said different wavelength channels and to direct each wavelength channel to one of the plurality of detectors.

29. (previously presented) An apparatus according to claim 23 and further comprising at least one variable optical attenuator arranged to provide controllable attenuation of the radiation received from said at least one optical fibre.

30. (previously presented) An apparatus according to claim 23 and further comprising at least one wavelength selective filter.

31. (previously presented) An apparatus according to claim 23 wherein at least one optical fibre attachment means comprises a mode matching means.

32. (previously presented) An apparatus according to claim 23 wherein at least one optical fibre attachment means is arranged to receive a lensed optical fibre.

33. (previously presented) An transmit/receive apparatus comprising transmitter apparatus as claimed in claim 1 and receiver apparatus.

34. (original) Apparatus according to claim 33 wherein said transmitter apparatus and said receiver apparatus are formed on a common substrate.

35. (previously presented) An apparatus according to claim 1 wherein the substrate comprises semiconductor material.

36. (original) An apparatus according to claim 35 wherein the substrate comprises a silicon on insulator (SOI) wafer.

37. (previously presented) An apparatus according to claim 1 formed by micro-fabrication techniques.

38. (original) An apparatus according to claim 37 wherein the micro-fabrication technique includes deep reactive ion etching.

39. (previously presented) An apparatus according to claim 1 wherein the hollow core optical waveguides are of substantially rectangular cross section.

40. (previously presented) An apparatus according to claim 1 wherein the hollow core optical waveguides are dimensioned to preferably guide radiation propagating in the fundamental mode.

41. (previously presented) An apparatus according to claim 1 wherein the hollow core optical waveguides are dimensioned to preferably guide radiation propagating in multiple optical modes.

42. (previously presented) An apparatus according to claim 1 wherein the internal surfaces of the hollow core optical waveguides carry a reflective coating.

43. (previously presented) An apparatus according to claim 1 wherein the substrate comprises a base portion and a lid portion.

44. (cancelled)

45. (cancelled)

46. (cancelled)